


GPS Engine Board Manual

SR-96

SiRF Star III

V 1.1.1



2008/08/08

service@dagamagps.com

www.dagamagps.com

Free service hot-line(for mainland):400-820-1322

Contents

1. Introduction	2
1.1 Overview.....	2
1.2 Features.....	2
2. Technical Specifications	2
2.1 Electrical Characteristics.....	2
2.2 Environmental Characteristics.....	3
3. Interface Specification.....	4
3.1 I/O Pin Description	4
3.2 PCB Layout	6
Appendix: Software Specifications	7

1. Introduction

1.1 Overview

SR-96 GPS module is a high performance receiver module for the Global Positioning System (GPS) solution providing latitude, longitude, height, time and velocity data. The smart type module has patch antenna, LNA (Low Noise amplifier) and saw filter. It has High performance and Low power consumption, extremely small size. The module design is base on low power consumption, high sensitivity SiRF Star III chipset. It can be easily embedded into portable devices for GPS wireless communication.

1.2 Features

- ☼ Full self-contained GPS receiver
- ☼ Fully shielded design
- ☼ Full implementation of SiRF Star III GPS architecture
- ☼ GSC3F/LP(High Performance GPS Single Chip)
- ☼ GPS DSP with integrated real time clock (RTC) ARM7TDMI CPU
- ☼ 4Mbit FLASH memory
- ☼ Low noise amplifier
- ☼ SAW filter
- ☼ TCXO

GPS receiver in a micro-component package

- ☼ Fully automatic assembly: Reflow solderable
- ☼ No RF connector
- ☼ Size: 13.1mm X 15.9mm X 2.7mm
- ☼ Weight: 1.1 grams

Ordering information:

SR-96-J GPS module with supply regulator enable, supply voltage 3.0~4.2V

SR-96-S GPS module without regulator, supply voltage 3.0~3.5V

2. Technical Specifications

2.1. Electrical Characteristics

2.1.1 General

Frequency	L1, 1575.42 MHz
C/A code	1.023 MHz chip rate
Channels	20 channels all in view tracking

2.1.2 Sensitivity

Tracking -159 dBm typical

2.1.3 Accuracy (Open Sky)

Position < 10 meters, 2D RMS
< 7 meters 2D RMS, WAAS corrected
1-5 meters, DGPS corrected
Time 1 microsecond synchronized to GPS time

2.1.4 Datum

Default WGS-84

2.1.5 Acquisition Rate (Open Sky)

Hot start 1 sec, average
Warm start 38 sec, average
Cold start 42 sec, average
Reacquisition 0.1 sec, average

2.1.6 Dynamic Conditions

Altitude < 18,000 meters (60,000 feet)
Velocity < 515 meters/sec (1000 knots)
Acceleration < 4 G
Jerk 20 meters/sec max

2.1.7 Power

Main power input 3.0 ~ 4.2 VDC input for SR-96J
3.0 ~ 3.5 VDC input for SR-96S
Supply Current 50~55mA

2.1.8 Serial Port

Electrical interface TTL level
Protocol support NMEA-0183, SiRF Binary
Default NMEA GGA, GSA, GSV, RMC, (GLL, VTG, and ZDA optional)
4800 baud rate (other rate optional)
8 bits data, 1 stop bit, no parity.

2.1.9 Time

1 PPS Pulse, pulse duration 1 μ s.
Time reference at the pulse positive edge.
Synchronized to GPS time, $\pm 1\mu$ s.

2.2. Environmental Characteristics

Operating temperature range -40 °C to +85 °C
Storage temperature range -45 °C to +100 °C

3. Interface Specification


3.1 I/O Pin Description for **SR-96J**

Pin	Name	Pin Description	I/O	Note
1	RF-IN	GPS signal from Antenna	I	50Ω (1.57542GHz)
2	GND	Ground		
3	GND	Ground		
4	GND	Ground		
5	V _{DD} RTC	Backup Power Input for RTC and SRAM	I	1.8~5.0V If Input voltage is below than 1.8V, V _{DD} RTC must be zero voltage
6	GND	Ground		
7	BOOT	Module boots into flash memory program mode if VCC during reset	I	Leave unconnected if not used. Use only factory production
8	GND	Ground		
9	GND	Ground		
10	GND	Ground		
11	VDD	Supply Voltage	I	3.0 ~ 4.2V
12	GND	Ground		
13	NC	Electrically Open		
14	GND	Ground		
15	GND	Ground		
16	NC	Electrically Open		
17	GND	Ground		
18	PEN	Supply regulator enable	I	Open or pull high (2.85~3.3V) for power enable (Internal 1MΩ Pull-up to VDD) Pull low (0V~1.0V) for power disable
19	GND	Ground		
20	NC	Electrically Open		
21	GND	Ground		
22	GND	Ground		
23	GND	Ground		
24	GND	Ground		
25	NC	Electrically Open		
26	GND	Ground		
27	NC	Electrically Open		
28	GND	Ground		
29	GND	Ground		
30	TXA	Serial Port A	O	
31	RXA	Serial Port A	I	Open if not used
32	NC	Electrically Open		
33	GND	Ground		
34	NC	Electrically Open		
35	GND	Ground		
36	GND	Ground		

I/O Pin Description for SR-96S

Pin	Name	Pin Description	I/O	Note
1	RF-IN	GPS signal from Antenna	I	50Ω (1.57542GHz)
2	GND	Ground		
3	GND	Ground		
4	GND	Ground		
5	V _{DD} RTC	Backup Power Input for RTC and SRAM	I	1.8~5.0V If Input voltage is below than 1.8V, V _{DD} RTC must be zero voltage
6	GND	Ground		
7	BOOT	Module boots into flash memory program mode if VCC during reset	I	Leave unconnected if not used. Use only factory production
8	GND	Ground		
9	GND	Ground		
10	GND	Ground		
11	VDD	Supply Voltage	I	3.0 ~ 3.5V
12	GND	Ground		
13	NC	Electrically Open		
14	GND	Ground		
15	GND	Ground		
16	NC	Electrically Open		
17	GND	Ground		
18	GPIO	General Purpose Input Output	I/O	
19	GND	Ground		
20	NC	Electrically Open		
21	GND	Ground		
22	GND	Ground		
23	GND	Ground		
24	GND	Ground		
25	NC	Electrically Open		
26	GND	Ground		
27	NC	Electrically Open		
28	GND	Ground		
29	GND	Ground		
30	TXA	Serial Port A	O	
31	RXA	Serial Port A	I	Open if not used
32	NC	Electrically Open		
33	GND	Ground		
34	NC	Electrically Open		
35	GND	Ground		
36	GND	Ground		

3.2 PCB Layout



Appendix: Software Specifications

NMEA Protocol

The software is capable of supporting the following NMEA message formats specifically developed and defined by SiRF.

NMEA Message Prefix	Format	Direction
\$GPGGA	Time, position and fix type data.	Out
\$GPGLL	Latitude, longitude, time of position fix and status.	Out
\$GPGSA	GNSS DOP and active satellites	Out
\$GPGSV	Satellites in view.	Out
\$GPMSS	Radio beacon signal-to-noise ratio, signal strength, frequency, etc.	Out
\$GPRMC	Recommended minimum specific GNSS data.	Out
\$GPVTG	Speed and course over ground.	Out
\$GPZDA	Date and time.	Out

General NMEA Format

The general NMEA format consists of an ASCII string commencing with a '\$' character and terminating with a <CR><LF> sequence. NMEA standard messages commence with 'GP' then a 3-letter message identifier. The message header is followed by a comma delimited list of fields optionally terminated with a checksum consisting of an asterix '*' and a 2 digit hex value representing the checksum. There is no comma preceding the checksum field. When present, the checksum is calculated as a bitwise exclusive of the characters between the '\$' and '*'. As an ASCII representation, the number of digits in each number will vary depending on the number and precision, hence the record length will vary. Certain fields may be omitted if they are not used, in which case the field position is reserved using commas to ensure correct interpretation of subsequent fields.

\$GPGGA

This message transfers global positioning system fix data. Following is an example.

\$GPGGA,161229.487,3723.2475,N,12158.3416,W,1,07,1.0,9.0,M,, ,0000*18

The \$GPGGA message structure is shown below:

Field	Example	Unit	Notes
Message ID	\$GPGGA		GGA protocol header.
UTC Time	161229.487		hhmmss.sss
Latitude	3723.2475		ddmm.mmmm
N/S Indicator	N		N=north or S=south.
Longitude	12158.3416		dddmm.mmmm
E/W indicator	W		E=east or W=west.
Position Fix Indicator	1		0: Fix not available or invalid. 1: GPS SPS mode, fix valid. 2: Differ. GPS, SPS mode, fix valid 3-5: Not supported. <i>6: Dead Reckoning Mode, fix valid. ⁽¹⁾</i>
Satellites Used	07		Number of satellites used to calculate fix. Range 0 to 12.
HDOP	1.0		Horizontal Dilution of Precision.
MSL Altitude ⁽²⁾	9.0	Meter	Altitude above mean seal level.
Units	M	Meter	M stands for “meters”.
Geoid Separation ⁽²⁾		Meter	Separation from Geoids can be blank.
Units		Meter	M stands for “meters”.
Age of Diff. Corr.		Second	Age in seconds. Blank (Null) fields when DGPS is not used.
Diff Ref. Station ID	0000		
Checksum	*18		
<CR> <LF>			Message terminator.

(1) Only apply to NMEA version 2.3 (and later) in this NMEA message description.

(2) SiRF does not support geoid corrections. Values are WGS84 ellipsoid heights.

\$GPGLL

This message transfers geographic position, latitude, longitude, and time. Following is an example.

\$GPGLL,3723.2475,N,12158.3416,W,161229.487,A,A*41

The \$GPGLL message structure is shown below:

Field	Example	Unit	Notes
Message ID	\$GPGLL		GLL protocol header.
Latitude	3723.2475		ddmm.mmmm
N/S Indicator	N		N=north or S=south.
Longitude	12158.3416		dddmm.mmmm
E/W indicator	W		E=east or W=west.
UTC Time	161229.487		hhmmss.sss
Status	A		A: Data valid or V: Data invalid.
<i>Mode</i>	<i>A</i>		<i>A=Autonomous, D=DGPS, E=DR (Only present in NMEA version 3.00).</i>
Checksum	*41		
<CR><LF>			Message terminator.

\$GPGSA

This message transfers DOP and active satellites information. Following is an example.

\$GPGSA,A,3,07,02,26,27,09,04,15, , , , ,1.8,1.0,1.5*33

The \$GPGSA message structure is shown below:

Field	Example	Unit	Notes
Message ID	\$GPGSA		GSA protocol header.
Mode	A		M: Manual, forced to operate in selected 2D or 3D mode. A: Automatic switching between modes.
Mode	3		1 Fix not available. 2 2D position fix. 3 3D position fix.
Satellites Used ⁽¹⁾	07		SV on channel 1.
Satellites Used ⁽¹⁾	02		SV on channel 2.
...			..
Satellites Used ⁽¹⁾			SV on channel 12.
PDOP	1.8		
HDOP	1.0		
VDOP	1.5		
Checksum	*33		
<CR> <LF>			Message terminator.

(1) Satellites used in solution.

\$GPGSV

This message transfers information about satellites in view. The \$GPGSV message structure is shown below. Each record contains the information for up to 4 channels, allowing up to 12 satellites in view. In the final record of the sequence the unused channel fields are left blank with commas to indicate that a field has been omitted. Following is an example.

\$GPGSV,2,1,07,07,79,048,42,02,51,062,43,26,36,256,42,27,27,138,42*71

\$GPGSV,2,2,07,09,23,313,42,04,19,159,41,15,12,041,42*41

The \$GPGSV message structure is shown below:

Field	Example	Unit	Notes
Message ID	\$GPGSV		GSA protocol header.
Number of messages ⁽¹⁾	2		Number of messages, maximum 3.
Message number	1		Sequence number, range 1 to 3.
Satellites in view	07		Number of satellites currently in view.
Satellite ID	07		Channel 1, ID range 1 to 32.
Elevation	79	degree	Elevation of satellite, maximum 90.
Azimuth	048	degree	Azimuth of satellite, range 0 to 359.
SNR (C/N ₀)	42	dBHz	Range 0 to 99, null when not tracking.
Satellite ID	02		Channel 2, ID range 1 to 32.
Elevation	51	degree	Elevation of satellite, maximum 90.
Azimuth	062	degree	Azimuth of satellite, range 0 to 359.
SNR (C/N ₀)	43	dBHz	Range 0 to 99, null when not tracking.
Satellite ID	26		Channel 3, ID range 1 to 32.
Elevation	36	degree	Elevation of satellite, maximum 90.
Azimuth	256	degree	Azimuth of satellite, range 0 to 359.
SNR (C/N ₀)	42	dBHz	Range 0 to 99, null when not tracking.
Satellite ID	27		Channel 4, ID range 1 to 32.
Elevation	27	degree	Elevation of satellite, maximum 90.
Azimuth	138	degree	Azimuth of satellite, range 0 to 359.
SNR (C/N ₀)	42	dBHz	Range 0 to 99, null when not tracking.
Checksum	*71		
<CR> <LF>			Message terminator.

(1) Depending on the number of satellites tracked multiple messages of GSV data may be required.

\$GPMSS

This message transfers information about radio beacon signal-to-noise ratio, signal strength, frequency, etc. Following is an example.

\$GPMSS,55,27,318.0,100,1,*57

The \$GPMSS message format is shown below.

Field	Example	Unit	Notes
Message ID	\$GPMSS		MSS protocol header.
Signal Strength	55	dB	SS of tracked frequency.
Signal-to-Noise Ratio	27	dB	SNR of tracked frequency.
Beacon Frequency	318.0	kHz	Currently tracked frequency.
Beacon Bit Rate	100		Bits per second.
<i>Channel Number ⁽¹⁾</i>	<i>1</i>		<i>The channel of the beacon being used if a multi-channel beacon receiver is used.</i>
Checksum	*57		
<CR> <LF>			Message terminator.

(1) Fields marked in italic red apply only to NMEA version 2.3 (and later) in this NMEA message description.

\$GPRMC

This message transfers recommended minimum specific GNSS data. Following is an example.

\$GPRMC,161229.487,A,3723.2475,N,12158.3416,W,0.13,309.62,120598,*,*10

The \$GPRMC message format is shown below.

Field	Example	Unit	Notes
Message ID	\$GPRMC		RMC protocol header.
UTC Time	161229.487		hhmmss.sss
Status	A		A: Data valid or V: Data invalid.
Latitude	3723.2475		ddmm.mmmm
N/S Indicator	N		N=north or S=south.
Longitude	12158.3416		ddmm.mmmm
E/W indicator	W		E=east or W=west.
Speed over ground	0.13	knot	Speed over ground
Course over ground	309.62	degree	Course over ground
Date	120598		ddmmyy, current date.
Magnetic variation ⁽¹⁾		degree	Not used.
<i>Mode ⁽²⁾</i>	<i>A</i>		<i>A=Autonomous, D=DGPS, E=DR.</i>
Checksum	*10		
<CR> <LF>			Message terminator.

(1) SiRF does not support magnetic declination. All “course over ground” data are geodetic WGS84 directions.

(2) Fields marked in italic red apply only to NMEA version 2.3 (and later) in this NMEA message description.

\$GPVTG

This message transfers velocity, course over ground, and ground speed. Following is an example.

\$GPVTG,309.62,T, ,M,0.13,N,0.2,K,A*23

The \$GPVTG message format is shown below.

Field	Example	Unit	Notes
Message ID	\$GPVTG		VTG protocol header.
Course (true)	309.62	degree	Measured heading
Reference	T		T = true heading
Course (magnetic)		degree	Measured heading
Reference ⁽¹⁾	M		M = magnetic heading ⁽¹⁾
Speed	0.13	knot	Speed in knots
Units	N		N = knots
Speed	0.2	km/hr	Speed
Units	K		K = km/hour.
<i>Mode ⁽²⁾</i>	<i>A</i>		<i>A=Autonomous, D=DGPS, E=DR.</i>
Checksum	*23		
<CR> <LF>			Message terminator.

(1) SiRF does not support magnetic declination. All “course over ground” data are geodetic WGS84 directions.

(2) Fields marked in italic red apply only to NMEA version 2.3 (and later) in this NMEA message description.

\$GPZDA

This message transfers UTC Time and Date. Following is an example.

\$GPZDA,181813,14,10,2003,00,00*4F

The \$GPZDA message format is shown below.

Field	Example	Unit	Notes
Message ID	\$GPZDA		ZDA protocol header.
UTC Time	181813		Either using valid IONO/UTC or estimated from default leap seconds.
UTC Day	14		01 to 31, day of month.
UTC Month	10		01 to 12.
UTC Year	2003		1980 to 2079.
Local zone hours	00		Offset from UTC (set to 00).
Local zone minutes	00		Offset from UTC (set to 00).
Checksum	*4F		
<CR> <LF>			Message terminator.

All Rights Reserved